


- ▲ Fixed lens / Mini-motorized lens available
- ▲ Auto Focus function
- ▲ Crystal Engine Gen3
- ▲ HDR Engine Gen3
- ▲ IR LED built in



Auto Focus

S5-N can perform fast, reliable auto focus and can adapt to different indoor and outdoor scenes through its unique algorithm. As auto focus can be done by camera itself, no on-site focus adjustment is required.



HDR Engine Gen3

The latest HDR engine delivers excellent, natural high dynamic images. Both details of high light and low light areas are kept, and no blending artifacts are generated.



Crystal Engine Gen3

Under extremely low light environment, Crystal engine gen3 delivers low noise, high quality image without compromising on details. In addition, it also keeps image sharp on motion object.



Features

- Multiple Progressive Scan CMOS Sensor support up to 5M Resolution
- Multi Exposure line-interleaved HDR
- Multi Codec support (H.265/ H.264/ MJPEG)
- Low Latency Streaming
- Quad Streams support
- True Day/Night function (ICR)
- IR LED (working distance up to 30m)
- 3D Motion Compensated Noise Reduction (MCTF)
- Smart Event function
 - External Input/ Motion Detection
 - Network Failure Detection/ Tampering Alarm
 - Periodical Event/ Manual Trigger/ Audio Detection
- Text Overlay and Privacy Masks
- Micro SD/ SDHC/ SDXC Card support
- ONVIF Profile S/ G/ T/ M support
- Smart Low Bitrate control
- Weatherproof (IP66)*

*optional

Custom Specification (Default)

OmniVision 5M		
Image Sensor	OmniVision 5M 1/2.7" Progressive CMOS	
Effective Pixels	HxV = 2720x1976 (5M)	
Pixel Size	2.0 μm	
Frame Rate (Maximum)	H.265	HDR 5M @30fps + 720p @30fps
	H.264	HDR 5M @30fps + 720p @30fps
	MJPEG	1080p @30fps
Lens : Default		
Minimum Illumination	Color	0.2 lux
	B/W	0 lux
Lens	Type	Motorized Lens, F1.6
	Focal Length	2.8-8mm
	Horizontal FOV	110.1° (wide), 53.1° (tele)
	Vertical FOV	74.6° (wide), 38.6° (tele)

Common Specification

Camera	
Day and Night	Automatically removable IR-cut filter
Shutter Time	1~1/10K sec.
HDR	Gen3 Engine
Zoom	digital zoom 10x
Image Settings	Color, Brightness, Sharpness, Contrast White Balance, Exposure Control 2DNR, 3DNR, NR by Motion Masking, Text Overlay
Image Rotation	90°, 180°, 270° rotation
Video Codec	
Compression	H.265/H.264/MJPEG
Streaming	Up to 4 individually configurable streams in H.265/ H.264/ MJPEG Configurable resolution/ frame rate/ bandwidth LBR/ VBR/ CBR in H.265/ H.264
Audio Codec	
Compression	G.711 / G.726 / AAC / LPCM
Streaming	2 way
Audio Input	Line in and Microphone built in*
Audio Output	Line out and Speaker built in*
Network	
Interface	10/100Mbps Ethernet
Security	User Authentication/ HTTPS/ IP Filter/IEEE 802.1x
Supported Protocols	ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, RTSPS, HTTP, HTTPS, FTP, NTP, DDNS, LLDP, RTMP, SRTP
ONVIF	Profile S / G / T / M conformant
System Integration	
Analytics	Motion Detection/ Tampering/ Audio detection
Event Triggers	External Input, Analytics, Network Failure Detection, Periodical Event, Manual Trigger
Event Actions	External output Activation Video and audio recording to edge storage File Upload : FTP, network share and email Notification HTTP, FTP, email

*. optional

General	
Casing	Metal Body
Power	PoE IEEE802.3af, class 0, max 9.60 watt DC12V, max 11.04 watt AC24V, max 9.56 watt, max 16.56 VA
Connectors	RJ45
	Alarm in x1, Alarm out x1, Terminal Block
	DC12V Terminal Block
	AC 24V Terminal Block
	Audio in Terminal Block(Indoor) Line In/3.5mm jack (Outdoor)
	Audio out Terminal Block(Indoor) Line Out/3.5mm jack (Outdoor)
	CVBS connector
IR Illumination	Illumination distance: 30m
Storage	Support for microSD/microSDHC/microSDXC card Support for recording to NAS
Operating Conditions	-30°C~55°C without heater -55°C~55°C with heater 10%~90%, No Condensation
Storage Conditions	-20°C~70°C
Approvals	EMC CE / FCC Environment IP66*
Dimensions	Ø117x82.9 mm
Weight	415 g