

- ▶ Deep Neural Network Accelerated Engine
- ▶ HDR Engine Gen3
- ▶ Crystal Engine Gen3
- ▶ IR LED built in
- ▶ Support 8M, 22x Optical Zoom
- ▶ Servo Feedback



DNN Edge Analytics

The latest computer vision technology makes DNN accelerated video processing engine efficient at the edge. This engine provides high accuracy, real-time object tracking and human face detection. Moreover, it allows simultaneous detection on multiple objects.



HDR Engine Gen3

The latest HDR engine delivers excellent, natural high dynamic images. Both details of high light and low light areas are kept, and no blending artifacts are generated.



Crystal Engine Gen3

Under extremely low light environment, Crystal engine gen3 delivers low noise, high quality image without compromising on details. In addition, it also keeps image sharp on motion object.



Features

- Sony Progressive Scan CMOS Sensor support 8M Resolution
- 8M, 22x Optical Zoom available
- Multi Exposure HDR
- Electrical Image Stabilizer (EIS) Support
- Multi Codec support (H.265/H.264/MJPEG)
- 3D Motion Compensated Noise Reduction
- IR LED (working distance up to 100m)
- ONVIF Profile S/G/T/M support
- Servo Feedback - Zero Drifting
- Deep Neural Network Accelerated Engine
 - Face/LPR Detection and Recognition
 - Object Classification and Recognition
 - People Detection and Tracking
- Smart Event function
 - External Input/Motion Detection
 - Network Failure Detection/Audio Detection
 - Periodical Event/Manual Trigger
- Vandal proof (IK10 Rating, excluding glass window)
- Weatherproof (IP66)

Custom Specification (Default)

Sony 4K			
Image Sensor	Sony 4K 1/1.8" Progressive CMOS		
Effective Pixels	HxV = 3864x2180 (4K)		
Pixel Size	2.0 μm		
Frame Rate (Maximum)	H.265	HDR 4K @30fps	+ d1 @30fps
	H.264	HDR 4K @30fps	+ d1 @30fps
	MJPEG	2M @30fps	
Lens : Default			
Minimum Illumination	Color	0.169 lux	
	B/W	0.113 lux	
Lens	Type	22x Zoom Lens, P-Iris, Auto-Iris, F1.5	
	Focal Length	6.4-138.5 mm	
	Horizontal FOV	62.6° (wide), 3.2° (tele)	
	Vertical FOV	36.7° (wide), 1.9° (tele)	

Common Specification

Camera		
Day and Night	Removable IR-cut filter	
Shutter Time	1~1/10K sec.	
HDR	Gen3 Engine	
EIS	Yes	
Digital Zoom	10x	
Image Settings	Exposure, White Balance, Brightness, Sharpness, Contrast, Saturation, Hue, IR Threshold, Noise Reduction, Backlight Compensation, Text Overlay, Privacy Mask	
Rotation	180° rotation	
Pan/Tilt		
Pan/Tilt Range	Pan : 0~360° endless	Tilt : -20~100°
Manual Speed	Pan : 0.1~90°/s	Tilt : 0.1~55°/s
Preset Speed	Pan : 300°/s	Tilt : 300°/s
Preset	256	
PTZ Mode	8 Sequence, 8 cruise, 4 auto pan	
Video Codec		
Compression	H.265/H.264/MJPEG	
Streaming	Up to 4 individually configurable streams in H.265/H.264/MJPEG Configurable resolution/frame rate/bandwidth LBR/VBR/CBR in H.265/H.264	
Audio Codec		
Compression	G.711/G.726/AAC/LPCM	
Streaming	2 way	
Audio Input	Line in	
Audio Output	Line out	
Network		
Interface	10/100/1000Mbps Ethernet	
Security	User Authentication/HTTPS/IP Filter/IEEE 802.1x	
Supported Protocols	ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, RTSPS, HTTP, HTTPS, FTP, NTP, DDNS, LLDP, RTMP, SRTP	
ONVIF	Profile S/G/T/M conformant	

System Integration	
Event Triggers	External Input, Analytics, Network Failure Detection, Periodical Event, Manual Trigger
Event Actions	External output Activation Video and audio recording to edge storage File Upload : FTP, network share and email Notification : HTTP, FTP, email
Intelligent Video Analytics	
General Analytics	Motion Detection/Audio Detection
DNN Analytics	Face Detection/Tracking/Recognition LPR Detection/Recognition People Detection and Tracking Human/Vehicle Classification Object Classification/Recognition

General		
Casing	Metal and Plastic	
Power	IEEE802.3bt, Type 3, class 6, max 51.00 watt AC24V, max 59.05 watt, max 87.12 VA	
Connectors	RJ45	
	AC24V, Terminal Block	
	Alarm in x4, Alarm out x2, Terminal Block	
	Audio in, Terminal Block	
IR Illumination Distance	100m	
	Support for microSD/microSDHC/microSDXC card Support for recording to NAS	
Operating Conditions	-40°C~50°C, with heater 10%~90%, No Condensation	
Storage Conditions	-20°C~70°C	
Approvals	EMC	CE/FCC
	Safety	RoHS
	Environment	IP66, IK10 ¹
Dimensions	Ø207x300 mm with Sunshield	
Weight	3.9 kg	

¹ IK10 rating excluding glass window

Custom Specification

Default

Sony 4K			
Image Sensor	Sony 4K 1/1.8" Progressive CMOS		
Effective Pixels	HxV = 3864x2180 (4K)		
Pixel Size	2.0 μm		
Frame Rate (Maximum)	H.265	HDR 4K @30fps	+ d1 @30fps
	H.264	HDR 4K @30fps	+ d1 @30fps
	MJPEG	2M @30fps	
Lens :			
Minimum Illumination	Color	0.169 lux	
	B/W	0.113 lux	
Lens	Type	22x Zoom Lens, P-Iris, Auto-Iris, F1.5	
	Focal Length	6.4-138.5 mm	
	Horizontal FOV	62.6° (wide), 3.2° (tele)	
	Vertical FOV	36.7° (wide), 1.9° (tele)	

Sony 4K			
Image Sensor	Sony 4K 1/1.8" Progressive CMOS		
Effective Pixels	HxV = 3856x2180 (4K)		
Pixel Size	2.0 μm		
Frame Rate (Maximum)	H.265	HDR 4K @30fps	+ d1 @30fps
	H.264	HDR 4K @30fps	+ d1 @30fps
	MJPEG	2M @30fps	
Lens :			
Minimum Illumination	Color	0.01 lux	
	B/W	0.007 lux	
Lens	Type	22x Zoom Lens, P-Iris, Auto-Iris, F1.5	
	Focal Length	6.4-138.5 mm	
	Horizontal FOV	62.1° (wide), 3.5° (tele)	
	Vertical FOV	36.1° (wide), 1.9° (tele)	

Sony 4K			
Image Sensor	Sony 4K 1/2.8" Progressive CMOS		
Effective Pixels	HxV = 3864x2192 (4K)		
Pixel Size	1.45 μm		
Frame Rate (Maximum)	H.265	HDR 4K @30fps	+ d1 @30fps
	H.264	HDR 4K @30fps	+ d1 @30fps
	MJPEG	2M @30fps	
Lens :			
Minimum Illumination	Color	0.203 lux	
	B/W	0.041 lux	
Lens	Type	30x Zoom Lens, P-Iris, Auto-Iris, F1.8	
	Focal Length	4.5-135 mm	
	Horizontal FOV	62.7° (wide), 2.5° (tele)	
	Vertical FOV	37.1° (wide), 1.4° (tele)	